6-1/4” HT 30k

Stand Alone Tong Configuration



6-1/4”-30k Tong
with Stand Alone Mounting Kit
P/N: 50.35.03.33.01
Quantity: _____

Tong with Backup Configuration



6-1/4”-30k Tong
with Backup Mounting Kit
P/N: 50.35.03.33.02
Quantity: _____



7”-45k Backup
P/N: 56.45.01.01
Quantity: _____

Accessories for Stand Alone Tong



Tension Load Cell
32-1/2” Handle, 45k Rated
P/N: 19-207400-152-SPT
Quantity: _____



Spring Hanger, 2000#
P/N: 11.85.000.00
Quantity: _____



Lift Cylinder Assembly
P/N: 200276
Quantity: _____

Accessories for Tong with Backup



Compression Load Cell
32-1/2” Handle, 45k Rated
P/N: 19-207120-145-SPT
Quantity: _____



Spring Hanger, 3000#
P/N: 11.85.000.01
Quantity: _____



Lift Cylinder Assembly
P/N: 200276
Quantity: _____


Tong Jaw and Die Selection


TONG DIE SELECTIONS			
PIPE SIZE	DIE PART NUMBER (MEDIUM TOOTH)	AVAILABILITY	QTY. TO ORDER
2-3/8"	27B.050.019.01	☑	
2-7/8"	27B.050.023.01	☑	
3-1/2"	27B.050.028.01	☑	
4"	27B.050.032.01	☑	
4-1/2"	27B.050.036.01	☑	
5"	27B.050.040.01	☑	
5-1/2"	27B.050.044.01	☑	
6"	27B.050.048.01	☑	
6-1/4"	27B.050.050.01	☑	
☑ = AVAILABLE ; ✪ = MADE TO ORDER			
2-3/8" thru 6-1/4"	20.050.050.W2 KIT	☑	
"20.050.050.W2 KIT" for use with 27B.050 Die Series			



Wrap Around Tong Jaw Kit
P/N: 20.050.050.W2 KIT
Quantity: _____

Wrap Around Dies are sold Individually.
Tong requires (2) dies while backups require (3) dies.





For complete listing of Tong Jaw Availability and Die Carrier Availability refer to “Jaw Reference Manual” available on the Starr Power Tongs Portal.

BACKUP DIE SELECTIONS			
PIPE SIZE	DIE PART NUMBER (MEDIUM TOOTH)	AVAILABILITY	QTY. TO ORDER
2-3/8"	27B.050.019.01	☑	
2-7/8"	27B.050.023.01	☑	
3-1/2"	27B.050.028.01	☑	
4"	27B.050.032.01	☑	
4-1/2"	27B.050.036.01	☑	
5"	27B.050.040.01	☑	
5-1/2"	27B.050.044.01	☑	
6"	27B.050.048.01	☑	
6-1/4"	27B.050.050.01	☑	
6-1/2"	27B.056.052.01	☑	
6-5/8"	27B.056.053.01	☑	
7"	27B.056.056.01	☑	
☑ = AVAILABLE ; ✪ = MADE TO ORDER			
27B.050 and 27B.056 Die Series fit directly to 7" Backup no additional Die Carriers required.			